

**FILON® RV FRP SIDEWALL**  
**AS MANUFACTURED BY KEMLITE COMPANY, INC.**

PRODUCT TYPE:	NOMINAL THICKNESS:	FINISH:
<b><u>RVF</u></b>  <b><u>RVP2</u></b>	<input type="checkbox"/> .045" (1.1 mm) <input type="checkbox"/> .05" (1.3 mm) <input type="checkbox"/> .06" (1.5 mm) <input type="checkbox"/> .07" (1.8 mm) <input type="checkbox"/> .075" (1.8 mm) <input type="checkbox"/> .08" (2.0 mm)	Smooth Gelcoated

OPTIONS:

- Gloss Finish:** (Per ASTM D523-60 Gloss Meter)
  - \_\_\_ Standard Gloss Finish shall be 80-90 Gloss Units
  - \_\_\_ Low Gloss Finish shall be 65-75 Gloss Units
- Widths up to and including 110" (2.8 m)**
- Lengths up to 500 lineal feet (152.4 m)**

PRODUCT SPECIFICATION:

- A written warranty must be supplied
- Physical property specifications must adhere to Kemlite technical bulletin #6279
- All panels (except embossed) shall have exclusive Filoplated® gelcoated finish for added weatherability
- Thickness tolerance shall be +/- 10% of specified nominal
- Allowable bend radius shall be 7" (178 mm) or greater
- Panels shall exhibit uniformity of color and gloss level as seen from 5' (1.5 m) distance
- Allowable color variation shall not exceed L ± 1.0, a ± 0.5, b ± 0.5 from pre-approved standard (See technical data #6320 for further information)

