



MSDS | Material Safety Data Sheet

Product Identification

Trade Name and Synonyms	Sanigrid® Fiberglass Ceiling Grid System
Chemical Name and Synonyms	Fiberglass Reinforced Plastic (frp)
Chemical Family	Polymerized Thermoset Polyesters
DOT Hazard Classification	Not Applicable

Composition/Information on Ingredients

The Sanigrid II ceiling system is composed of a mixture of isophthalic polyester resin, inorganic fillers, processing additives, and fiberglass reinforcement. During the manufacturing process, this mixture is cured or hardened into a stable, solid material that is non-hazardous when handled or processed in accordance with good manufacturing and industrial hygiene practices.

Hazards Identification

Threshold Limit Value (TLV)	Fabricating, cutting, drilling, etc. of frp may produce dust, which should be controlled. Particulate level should not exceed 30M ppcf.
Primary Route of Entry	Inhalation of or skin contact with dust.
Effects of Overexposure	Exposure to dust in excess of TLV may result in skin or upper respiratory tract irritation. Pre-existing skin or respiratory disorders may cause more susceptibility to these effects.

Physical Data

Boiling Point	Not applicable
Vapor Pressure	Not applicable
Vapor Density	Not applicable
Specific Gravity (water=1)	1.6 g/cm ³
% Volatile (by volume)	Not applicable
Solubility in Water	Insoluble

First Aid Measures

Inhalation of Dust	Remove from source of exposure into fresh air. Ensure clear airway. Get medical help.
Prolonged Skin Contact	Remove contaminated clothing. Wash skin with warm water and soap. Skin cream could be helpful.
Eye Contact	Flush with running water for 15 minutes or more.
Ingestion of Dust	Do not induce vomiting. Get medical help.

Fire and Explosion Data

Flash Point

Ignition Temperature

Extinguishing Media

Fire Fighting Procedures

Not Applicable.

Typically 650°F or higher for frp panels.

Water, CO², dry chemical.

Use media best suited to fire environment. Use water to cool fire-exposed containers and to flush spills from ignition sources. Use self-contained breathing apparatus for large scale fires.

Unusual Fire or Explosion Hazards

As with other building materials, combustion will yield toxic materials such as carbon monoxide (CO) and carbon dioxide (CO²), and may also yield aliphatic and aromatic hydrocarbons and halogenated compounds.

Decomposition Products

Under fire conditions only, fumes may contain carbon monoxide and halogens.

Reactivity Data

This material is stable. Hazardous polymerization will not occur. Organic solvents soften material if allowed to be in contact for a prolonged length of time.

Environmental Information

Transportation Data

Special Precautions

Most cured polyesters have little or no toxic effect. If curing is incomplete, there may be residues of toxic peroxides or styrene monomers.

No special regulations govern transportation of this product.

Dispose of in accordance with local, provincial, and federal regulations.

Incinerate only at approved disposal sites.

Personal Protection Information

Respiratory Protection

Eye Protection

Skin Protection


Use adequate ventilation to control dust when machining, cutting, drilling, etc. Cover nose and mouth with mask approved by NIOSH/OSHA.

Use goggles or safety glasses when machining, cutting, drilling, etc.

Have eye washes available.

Wear protective gloves, long pants and long sleeves when machining, cutting, drilling, etc. Wash skin with soap and water after handling. Wash dusty work clothes separately.

Approved By



Date

8/1/2010

www.cranecomposites.com | 1.800.435.0080 | 1.815.467.8600 | sales@cranecomposites.com

Crane Composites is the manufacturer of Glasbord, Filon, Sequentia, ArmorTuf and a variety of other fiberglass reinforced plastic (frp) composite panels. Inspired by the Kemplite tradition, Crane Composites has over 55 years of industry experience and is a recognized industry leader in frp applications.

We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions of use are beyond our control, all risks are assumed by the user. Nothing herein shall be construed as a recommendation for uses which infringe on valid patents or as extending a license under valid patents.

Form 6241 | Rev. 4 | 7.10 | (5567)

