



Composites

technical data  
7808

## PRE-TOOLING mist

PRODUCT CODE: CRM

COLOR RITE™ MIST



### DESCRIPTION

Color Rite's Mist is available through Crane Composites for color-matched professional looking panel installations. Pre-Tooling Mist is a spray agent used to aid in caulk installations. It is low odor, easy to apply and user friendly. Pre-Tooling Mist helps keep excess caulk from adhering to the FRP panel.

### INSTALLATION (USING COLOR RITE'S COLOR SIL CAULK AND PRE-TOOLING MIST)

DO NOT SPRAY ON SURFACE PRIOR TO CAULKING. PRE-TOOLING MIST PREVENTS SILICONE ADHESION. DO NOT SPRAY ON UNCAULKED AREAS PRIOR TO SILICONE APPLICATION. TESTING PRODUCT IN AN INCONSPICUOUS AREA IS RECOMMENDED.

1. When using caulk and sealant, all panels are installed prior to the seam treatment. Before caulk and sealant can be applied, installed panels need to be adhered for a minimum of 6 hours, but 24 hours is recommended when room temperature is at 72°F and 45%-50% humidity
2. Prep surface according to silicone instructions. Apply bead of silicone to desired surface.
3. Lightly spray Pre-Tooling Mist directly onto silicone bead, approximately 6-8 inches away. The goal is to lightly cover not only the silicone bead, but also the surface on either side of it. DO NOT SATURATE EITHER THE SILICONE OR THE SURFACE TO WHICH IT IS BEING APPLIED. It is also recommended to lightly spray the tool being used to tool the silicone bead.
4. Using moderate pressure, move the tool along the silicone to smooth and press the silicone bead into the intended void. Intermittent removal of excess silicone is suggested for best performance.
5. Using a clean, damp cloth, softly wipe away any excess Pre-Tooling Mist from the applied surface. Be careful not to wipe away the curing silicone caulk.

SEE OUR INSTALLATION VIDEO AT  
[cranecomposites.com/caulkinstall](http://cranecomposites.com/caulkinstall)



A global leading provider of resilient wall and ceiling coverings. Kemlite® was established in 1954 and the company changed names to Crane Composites in 2007. Crane Composites is headquartered in Channahon, IL and all our products are manufactured in the United States. We work with hundreds of distributors, ensuring our products are easily accessible and readily available to our customers.

The following are trademarks of Crane Composites, Inc. or a related company: Glasbord, Kemlite, Kemply, Surfaseal, Sanigridd, Silhouette Trims and Varietex



[cranecomposites.com](http://cranecomposites.com) | 1.800.435.0080 | [sales@cranecomposites.com](mailto:sales@cranecomposites.com)

